



Standart Features

- Advanced digital electronic control providing safety stop switch
- Remote start/stop plug-in connection
- Electronic governing
- Safety shut-downs: overspeed, low oil pressure and high coolant temperature
- Water cooled exhaust mixing elbow
- Freshwater cooling system with heat exchanger, expansion tank
- Gear driven raw water pump
- Anti-vibration mounts - fail safe rubber type

Engine Features

The Diesel Engine demonstrates a superior applicability for marine gensets. It has the best level of sound attenuation in its class, achieved by the optimal design of the fuel system and the thorough structural analysis of each component.

Alternator Features

The alternator is designed to be suitable for typical generator marine applications. Standard winding protection for clean environments with relative humidity $\leq 95\%$, including indoor marine environments.

Electrical Characteristics

	50 Hz	60 Hz
Voltage (V)	220	277
KW	5,5	6,6
RPM	3000	3600

Engine Details: Lombardini Idw 502

Engine Type	4-stroke,diesel
Cylinder Configuration	2 in-line
Bore x Stroke (mm)	72x65
Total Displacement (cm3)	505
Aspiration	natural
Dry Weight (kg)	70
Cooling System	water-cooled
Combustion System	indirect injection
Fuel Injection System	pump-line-nozzle
Electrical System (V/A)	12 / 65
Starting System (V/kW)	12 / 1.7
Rotation (1204)	counterclockwise
Flywheel and housing	semi: SAE 7.5" / SAE #5

Alternator Details: meccalte ecp3 1s2

Insulation class	H
Winding pitch	2/3 (wdg 6)
Phase	1 ph.
Number of wires	12
Protection	IP23
Altitude	≤ 1000 m
Overspeed	2250 min-1
Air flow	6,4 m3/min, 50 Hz - 7,8 m3/s, 60 Hz

Fuel Consumption	3000 rpm	3600 rpm
%100 load (g/kwh)	326	326

Control & Monitoring

- Over/Under frequency
- Over/Under voltage
- Over/Under speed
- High temperature
- Oil pressure
- Running hours
- 10 events, warnings or shutdown alarms with running hours stamp
- 3 configurable analog inputs with wide list of predefined senders



Generator Weights and Dimensions

	Without Sound Shield	With Sound Shield
Weight (kg)	141	198
Length (mm)	849	990
Width (mm)	360	480
Height (mm)	505	660